



## 2" W.G. Flat Oval Construction For 12" Minor

Stock Diameter	Order Size	Equivalent Round	Spiral Seam Gauge	Fitting Gauge	M/F Joint *Optional Tie Rod for Easy Install	Reinforcement Max. Spacing
18Ø	<b>22x12</b>	17.37Ø	24ga	20ga	N/R	N/R
20Ø	<b>25x12</b>	18.47Ø	22ga	20ga	N/R	N/R
22Ø	<b>28x12</b>	19.16Ø	22ga	20ga	N/R	N/R
24Ø	<b>31x12</b>	20.12Ø	22ga	20ga	N/R	C @ 10'
26Ø	<b>34x12</b>	21.02Ø	22ga	20ga	N/R	D @ 10'
28Ø	<b>37x12</b>	21.86Ø	22ga	18ga	1 - 1/2" Tie Rods	E @ 10'
30Ø	<b>40x12</b>	22.65Ø	22ga	18ga	1 - 1/2" Tie Rods	E @ 6'
32Ø	<b>43x12</b>	23.40Ø	22ga	18ga	1 - 1/2" Tie Rods	F @ 6'
34Ø	<b>47x12</b>	24.53Ø	22ga	18ga	1 - 1/2" Tie Rods	F @ 6'
36Ø	<b>50x12</b>	25.03Ø	20ga	18ga	1 - 1/2" Tie Rods	G @ 6'
38Ø	<b>53x12</b>	25.67Ø	20ga	18ga	1 - 1/2" Tie Rods	G @ 6'
40Ø	<b>56x12</b>	26.29Ø	20ga	18ga	1 - 1/2" Tie Rods	H @ 6'
42Ø	<b>59x12</b>	26.89Ø	20ga	18ga	1 - 1/2" Tie Rods	H @ 6'
44Ø	<b>62x12</b>	27.47Ø	20ga	16ga	2 - 1/2" Tie Rods	H @ 5'
46Ø	<b>65x12</b>	28.03Ø	20ga	16ga	2 - 1/2" Tie Rods	H @ 5'
48Ø	<b>69x12</b>	28.74Ø	20ga	16ga	2 - 1/2" Tie Rods	I @ 5'
50Ø	<b>72x12</b>	29.26Ø	18ga	16ga	2 - 1/2" Tie Rods	I @ 6'
52Ø	<b>75x12</b>	29.77Ø	18ga	16ga	2 - 1/2" Tie Rods	J @ 5'
54Ø	<b>78x12</b>	30.08Ø	18ga	16ga	2 - 1/2" Tie Rods	J @ 5'