



## 2" W.G. Flat Oval Construction For 14" Minor

Stock Diameter	Order Size	Equivalent Round	Spiral Seam Gauge	Fitting Gauge	M/F Joint *Optional Tie Rod for Easy Install	Reinforcement Max. Spacing
18Ø	<b>20X14</b>	17.32Ø	24ga	20ga	N/R	N/R
20Ø	<b>23X14</b>	18.69Ø	24ga	20ga	N/R	N/R
22Ø	<b>27X14</b>	20.32Ø	22ga	20ga	N/R	N/R
24Ø	<b>30X14</b>	21.43Ø	22ga	20ga	N/R	N/R
26Ø	<b>33X14</b>	22.46Ø	22ga	20ga	N/R	C @ 10'
28Ø	<b>36X14</b>	23.42Ø	22ga	20ga	1 - 1/2" Tie Rods	D @ 10'
30Ø	<b>39X14</b>	24.33Ø	22ga	18ga	1 - 1/2" Tie Rods	E @ 10'
32Ø	<b>42X14</b>	25.18Ø	22ga	18ga	1 - 1/2" Tie Rods	E @ 6'
34Ø	<b>45X14</b>	25.99Ø	22ga	18ga	1 - 1/2" Tie Rods	F @ 6'
36Ø	<b>49X14</b>	27.02Ø	20ga	18ga	1 - 1/2" Tie Rods	G @ 8'
38Ø	<b>52X14</b>	27.75Ø	20ga	18ga	1 - 1/2" Tie Rods	G @ 6'
40Ø	<b>55X14</b>	28.45Ø	20ga	18ga	1 - 1/2" Tie Rods	G @ 6'
42Ø	<b>58X14</b>	29.12Ø	20ga	18ga	1 - 1/2" Tie Rods	H @ 6'
44Ø	<b>61X14</b>	29.77Ø	20ga	16ga	2 - 1/2" Tie Rods	H @ 6'
46Ø	<b>64X14</b>	30.40Ø	20ga	16ga	2 - 1/2" Tie Rods	H @ 5'
48Ø	<b>67X14</b>	31.01Ø	20ga	16ga	2 - 1/2" Tie Rods	H @ 5'
50Ø	<b>71X14</b>	31.79Ø	18ga	16ga	2 - 1/2" Tie Rods	I @ 6'
52Ø	<b>74X14</b>	32.36Ø	18ga	16ga	2 - 1/2" Tie Rods	I @ 6'
54Ø	<b>77X14</b>	32.91Ø	18ga	16ga	2 - 1/2" Tie Rods	J @ 5'