



## 2" W.G. Flat Oval Construction For 16" Minor

Stock Diameter	Order Size	Equivalent Round	Spiral Seam Gauge	Fitting Gauge	M/F Joint *Optional Tie Rod for Easy Install	Reinforcement Max. Spacing
20∅	<b>22X16</b>	19.38∅	24ga	20ga	N/R	N/R
22∅	<b>25X16</b>	20.80∅	22ga	20ga	N/R	N/R
24∅	<b>29X16</b>	22.50∅	22ga	20ga	N/R	N/R
26∅	<b>32X16</b>	23.66∅	22ga	20ga	N/R	N/R
28∅	<b>35X16</b>	24.74∅	22ga	20ga	N/R	C @ 10'
30∅	<b>38X16</b>	25.60∅	22ga	18ga	1 - 1/2" Tie Rods	D @ 10'
32∅	<b>41X16</b>	26.72∅	22ga	18ga	1 - 1/2" Tie Rods	E @ 10'
34∅	<b>44X16</b>	27.36∅	22ga	18ga	1 - 1/2" Tie Rods	E @ 6'
36∅	<b>47X16</b>	28.50∅	22ga	18ga	1 - 1/2" Tie Rods	F @ 6'
38∅	<b>51X16</b>	29.59∅	20ga	18ga	1 - 1/2" Tie Rods	G @ 8'
40∅	<b>54X16</b>	30.37∅	20ga	18ga	1 - 1/2" Tie Rods	G @ 6'
42∅	<b>57X16</b>	31.12∅	20ga	18ga	1 - 1/2" Tie Rods	G @ 6'
44∅	<b>60X16</b>	31.85∅	20ga	18ga	1 - 1/2" Tie Rods	H @ 6'
46∅	<b>63X16</b>	32.55∅	20ga	16ga	2 - 1/2" Tie Rods	H @ 6'
48∅	<b>66X16</b>	33.22∅	20ga	16ga	2 - 1/2" Tie Rods	H @ 5'
50∅	<b>69X16</b>	33.87∅	20ga	16ga	2 - 1/2" Tie Rods	H @ 5'
52∅	<b>73X16</b>	34.72∅	18ga	16ga	2 - 1/2" Tie Rods	I @ 6'
54∅	<b>76X16</b>	35.33∅	18ga	16ga	2 - 1/2" Tie Rods	I @ 6'
56∅	<b>79X16</b>	35.89∅	18ga	16ga	2 - 1/2" Tie Rods	J @ 5'