



## 2" W.G. Flat Oval Construction For 20" Minor

Stock Diameter	Order Size	Equivalent Round	Spiral Seam Gauge	Fitting Gauge	<u>M/F Joint</u> *Optional Tie Rod for Easy Install	Reinforcement Max. Spacing
24∅	<b>26X20</b>	23.46∅	22ga	20ga	N/R	N/R
26∅	<b>29X20</b>	24.95∅	22ga	20ga	N/R	N/R
28∅	<b>33X20</b>	26.77∅	22ga	20ga	N/R	N/R
30∅	<b>36X20</b>	28.02∅	22ga	20ga	N/R	N/R
32∅	<b>39X20</b>	29.20∅	22ga	18ga	1 - 1/2" Tie Rods	C @ 10'
34∅	<b>42X20</b>	30.31∅	22ga	18ga	1 - 1/2" Tie Rods	D @ 10'
36∅	<b>45X20</b>	31.36∅	22ga	18ga	1 - 1/2" Tie Rods	E @ 10'
38∅	<b>48X20</b>	32.37∅	20ga	18ga	1 - 1/2" Tie Rods	F @ 10'
40∅	<b>51X20</b>	33.32∅	20ga	18ga	1 - 1/2" Tie Rods	G @ 8'
42∅	<b>55X20</b>	34.54∅	20ga	18ga	1 - 1/2" Tie Rods	G @ 8'
44∅	<b>58X20</b>	35.41∅	20ga	18ga	1 - 1/2" Tie Rods	G @ 6'
46∅	<b>61X20</b>	36.25∅	20ga	16ga	2 - 1/2" Tie Rods	G @ 6'
48∅	<b>64X20</b>	37.06∅	20ga	16ga	2 - 1/2" Tie Rods	H @ 6'
50∅	<b>67X20</b>	37.84∅	20ga	16ga	2 - 1/2" Tie Rods	H @ 6'
52∅	<b>71X20</b>	38.84∅	18ga	16ga	2 - 1/2" Tie Rods	I @ 6'
54∅	<b>74X20</b>	39.57∅	18ga	16ga	2 - 1/2" Tie Rods	I @ 6'
56∅	<b>77X20</b>	40.17∅	18ga	16ga	2 - 1/2" Tie Rods	I @ 6'
58∅	<b>80X20</b>	40.90∅	18ga	16ga	2 - 1/2" Tie Rods	I @ 6'
60∅	<b>83X20</b>	41.60∅	18ga	16ga	2 - 1/2" Tie Rods	J @ 5'