



2" W.G. Flat Oval Construction For 6" Minor

Stock Diameter	Order Size	Equivalent Round	Spiral Seam Gauge	Fitting Gauge	<u>M/F Joint</u> *Optional Tie Rod for Easy Install	Reinforcement Max. Spacing
16Ø	22 x 6	11.82Ø	24ga	20ga	N/R	N/R
18Ø	25 x 6	12.51Ø	22ga	20ga	N/R	C @ 10'
20Ø	28 x 6	13.51Ø	22ga	20ga	N/R	D @ 10'
22Ø	31 x 6	13.73Ø	22ga	20ga	N/R	E @ 10'
24Ø	34 x 6	14.28Ø	22ga	20ga	N/R	E @ 6'
26Ø	37 x 6	14.80Ø	22ga	18ga	1 - 1/2" Tie Rod	F @ 6'
28Ø	41 x 6	15.45Ø	22ga	18ga	1 - 1/2" Tie Rod	F @ 6'
30Ø	44 x 6	15.90Ø	22ga	18ga	1 - 1/2" Tie Rod	G @ 5'
32Ø	47 x 6	16.34Ø	22ga	18ga	1 - 1/2" Tie Rod	G @ 5'
34Ø	50 x 6	16.76Ø	20ga	18ga	1 - 1/2" Tie Rod	H @ 6'
36Ø	53 x 6	17.16Ø	20ga	18ga	1 - 1/2" Tie Rod	H @ 6'
38Ø	56 x 6	17.55Ø	20ga	18ga	1 - 1/2" Tie Rod	H @ 5'
40Ø	59 x 6	17.92Ø	20ga	18ga	1 - 1/2" Tie Rod	H @ 5'
42Ø	63 x 6	18.40Ø	20ga	16ga	2 - 1/2" Tie Rods	I @ 5'
44Ø	66 x 6	18.75Ø	20ga	16ga	2 - 1/2" Tie Rods	I @ 5'
46Ø	69 x 6	19.08Ø	20ga	16ga	2 - 1/2" Tie Rods	I @ 4'
48Ø	72 x 6	19.41Ø	18ga	16ga	2 - 1/2" Tie Rods	J @ 5'
50Ø	75 x 6	19.73Ø	18ga	16ga	2 - 1/2" Tie Rods	J @ 5'
52Ø	79 x 6	21.60Ø	18ga	16ga	2 - 1/2" Tie Rods	I @ 4'