



## 4" W.G. Flat Oval Construction For 10" Minor

Stock Diameter	Order Size	Equivalent Round	Spiral Seam Gauge	Fitting Gauge	<u>M/F Joint</u>	
					*Optional Tie Rod for Easy Install	Reinforcement Max. Spacing
18∅	<b>23x10</b>	15.85∅	22ga	20ga	N/R	C @ 8'
20∅	<b>26x10</b>	16.82∅	22ga	20ga	N/R	D @ 8'
22∅	<b>29x10</b>	17.17∅	22ga	20ga	N/R	E @ 6'
24∅	<b>32x10</b>	18.53∅	22ga	20ga	N/R	E @ 5'
26∅	<b>35x10</b>	19.30∅	22ga	20ga	N/R	F @ 5'
28∅	<b>38x10</b>	20.02∅	22ga	18ga	1 - 1/2" Tie Rods	F @ 5'
30∅	<b>41x10</b>	20.71∅	22ga	18ga	1 - 1/2" Tie Rods	G @ 4'
32∅	<b>45x10</b>	21.57∅	22ga	18ga	1 - 1/2" Tie Rods	G @ 4'
34∅	<b>48x10</b>	22.18∅	22ga	18ga	1 - 1/2" Tie Rods	G @ 3'
36∅	<b>51x10</b>	22.76∅	20ga	18ga	1 - 1/2" Tie Rods	H @ 4'
38∅	<b>54x10</b>	23.32∅	20ga	18ga	1 - 1/2" Tie Rods	H @ 3'
40∅	<b>57x10</b>	23.86∅	20ga	18ga	1 - 1/2" Tie Rods	H @ 3'
42∅	<b>60x10</b>	24.39∅	20ga	16ga	1 - 1/2" Tie Rods	I @ 3'
44∅	<b>63x10</b>	24.89∅	20ga	16ga	2 - 1/2" Tie Rods	I @ 3'
46∅	<b>67x10</b>	25.54∅	20ga	16ga	2 - 1/2" Tie Rods	I @ 3'
48∅	<b>70x10</b>	26.00∅	20ga	16ga	2 - 1/2" Tie Rods	I @ 3'
50∅	<b>73x10</b>	26.46∅	18ga	16ga	2 - 1/2" Tie Rods	J @ 3'
52∅	<b>76x10</b>	26.90∅	18ga	16ga	2 - 1/2" Tie Rods	J @ 3'
54∅	<b>80x10</b>	27.35∅	18ga	16ga	2 - 1/2" Tie Rods	J @ 3'