



4" W.G. Flat Oval Construction For 8" Minor

Stock Diameter	Order Size	Equivalent Round	Spiral Seam Gauge	Fitting Gauge	<u>M/F Joint</u>	Reinforcement Max. Spacing
					*Optional Tie Rod for Easy Install	
18∅	24x8	14.39∅	22ga	20ga	N/R	D @ 8'
20∅	27x8	15.19∅	22ga	20ga	N/R	E @ 6'
22∅	30x8	15.92∅	22ga	20ga	N/R	E @ 5'
24∅	33x8	16.61∅	22ga	20ga	N/R	F @ 5'
26∅	36x8	17.25∅	22ga	18ga	N/R	F @ 5'
28∅	39x8	17.86∅	22ga	18ga	1 - 1/2" Tie Rods	G @ 4'
30∅	43x8	18.62∅	22ga	18ga	1 - 1/2" Tie Rods	G @ 4'
32∅	46x8	19.16∅	22ga	18ga	1 - 1/2" Tie Rods	G @ 3'
34∅	49x8	19.68∅	22ga	18ga	1 - 1/2" Tie Rods	G @ 3'
36∅	52x8	20.17∅	20ga	18ga	1 - 1/2" Tie Rods	H @ 3'
38∅	55x8	20.65∅	20ga	18ga	1 - 1/2" Tie Rods	H @ 3'
40∅	58x8	21.11∅	20ga	18ga	1 - 1/2" Tie Rods	I @ 3'
42∅	61x8	21.55∅	20ga	16ga	1 - 1/2" Tie Rods	I @ 3'
44∅	65x8	22.12∅	20ga	16ga	2 - 1/2" Tie Rods	I @ 3'
46∅	68x8	22.53∅	20ga	16ga	2 - 1/2" Tie Rods	I @ 3'
48∅	71x8	22.93∅	18ga	16ga	2 - 1/2" Tie Rods	J @ 3'
50∅	74x8	23.31∅	18ga	16ga	2 - 1/2" Tie Rods	J @ 3'
52∅	78x8	23.70∅	18ga	16ga	2 - 1/2" Tie Rods	J @ 3'
54∅	81x8	24.00∅	18ga	16ga	2 - 1/2" Tie Rods	J @ 2.5'