



## 2" W.G. Flat Oval Construction For 18" Minor

Stock Diameter	Order Size	Equivalent Round	Spiral Seam Gauge	Fitting Gauge	<u>M/F Joint</u> *Optional Tie Rod for Easy Install	Reinforcement Max. Spacing
22Ø	<b>24X18</b>	21.42Ø	24ga	20ga	N/R	N/R
24Ø	<b>27X18</b>	22.88Ø	22ga	20ga	N/R	N/R
26Ø	<b>31X18</b>	24.64Ø	22ga	20ga	N/R	N/R
28Ø	<b>34X18</b>	28.85Ø	22ga	20ga	N/R	N/R
30Ø	<b>37X18</b>	26.99Ø	22ga	18ga	1 - 1/2" Tie Rods	C @ 10'
32Ø	<b>40X18</b>	28.05Ø	22ga	18ga	1 - 1/2" Tie Rods	D @ 10'
34Ø	<b>43X18</b>	29.06Ø	22ga	18ga	1 - 1/2" Tie Rods	E @ 10'
36Ø	<b>46X18</b>	30.02Ø	22ga	18ga	1 - 1/2" Tie Rods	E @ 6'
38Ø	<b>49X18</b>	30.94Ø	20ga	18ga	1 - 1/2" Tie Rods	G @ 8'
40Ø	<b>53X18</b>	32.10Ø	20ga	18ga	1 - 1/2" Tie Rods	G @ 8'
42Ø	<b>56X18</b>	32.92Ø	20ga	18ga	1 - 1/2" Tie Rods	G @ 6'
44Ø	<b>59X18</b>	33.72Ø	20ga	18ga	1 - 1/2" Tie Rods	G @ 6'
46Ø	<b>62X18</b>	34.49Ø	20ga	16ga	2 - 1/2" Tie Rods	H @ 6'
48Ø	<b>65X18</b>	35.23Ø	20ga	16ga	2 - 1/2" Tie Rods	H @ 6'
50Ø	<b>68X18</b>	35.95Ø	20ga	16ga	2 - 1/2" Tie Rods	H @ 5'
52Ø	<b>72X18</b>	36.87Ø	18ga	16ga	2 - 1/2" Tie Rods	I @ 6'
54Ø	<b>75X18</b>	37.54Ø	18ga	16ga	2 - 1/2" Tie Rods	I @ 6'
56Ø	<b>78X18</b>	38.12Ø	18ga	16ga	2 - 1/2" Tie Rods	I @ 6'
58Ø	<b>81X18</b>	38.79Ø	18ga	16ga	2 - 1/2" Tie Rods	J @ 5'