



2" W.G. Flat Oval Construction For 22" Minor

Stock Diameter	Order Size	Equivalent Round	Spiral Seam Gauge	Fitting Gauge	<u>M/F Joint</u> *Optional Tie Rod for Easy Install	Reinforcement Max. Spacing
26∅	28x22	25.49∅	22ga	20ga	N/R	N/R
28∅	31x22	27.01∅	22ga	20ga	N/R	N/R
30∅	35x22	28.87∅	22ga	20ga	N/R	N/R
32∅	38x22	30.16∅	22ga	18ga	1 - 1/2" Tie Rods	N/R
34∅	41x22	32.53∅	22ga	18ga	1 - 1/2" Tie Rods	C @ 10'
36∅	44x22	30.31∅	22ga	18ga	1 - 1/2" Tie Rods	D @ 10'
38∅	47x22	33.63∅	22ga	18ga	1 - 1/2" Tie Rods	E @ 10'
40∅	50x22	34.67∅	20ga	18ga	1 - 1/2" Tie Rods	F @ 10'
42∅	53x22	35.67∅	20ga	18ga	1 - 1/2" Tie Rods	G @ 8'
44∅	57x22	36.94∅	20ga	18ga	1 - 1/2" Tie Rods	G @ 8'
46∅	60x22	37.85∅	20ga	18ga	1 - 1/2" Tie Rods	G @ 6'
48∅	63x22	38.72∅	20ga	16ga	2 - 1/2" Tie Rods	G @ 6'
50∅	66x22	39.57∅	20ga	16ga	2 - 1/2" Tie Rods	H @ 6'
52∅	69x22	40.39∅	20ga	16ga	2 - 1/2" Tie Rods	H @ 6'
54∅	73x22	41.44∅	18ga	16ga	2 - 1/2" Tie Rods	I @ 6'
56∅	76x22	42.21∅	18ga	16ga	2 - 1/2" Tie Rods	I @ 6'
58∅	79x22	42.84∅	18ga	16ga	2 - 1/2" Tie Rods	I @ 6'
60∅	82x22	43.60∅	18ga	16ga	2 - 1/2" Tie Rods	I @ 6'