



## 2" W.G. Flat Oval Construction For 24" Minor

Stock Diameter	Order Size	Equivalent Round	Spiral Seam Gauge	Fitting Gauge	<u>M/F Joint</u> *Optional Tie Rod for Easy Install	Reinforcement Max. Spacing
28∅	<b>30x24</b>	27.52∅	22ga	20ga	N/R	N/R
30∅	<b>33x24</b>	29.07∅	22ga	20ga	N/R	N/R
32∅	<b>37x24</b>	30.97∅	22ga	18ga	1 - 1/2" Tie Rods	N/R
34∅	<b>40x24</b>	32.29∅	22ga	18ga	1 - 1/2" Tie Rods	N/R
36∅	<b>43x24</b>	33.54∅	22ga	18ga	1 - 1/2" Tie Rods	C @ 10'
38∅	<b>46x24</b>	34.73∅	22ga	18ga	1 - 1/2" Tie Rods	D @ 10'
40∅	<b>49x24</b>	35.86∅	20ga	8ga	1 - 1/2" Tie Rods	E @ 10'
42∅	<b>52x24</b>	36.94∅	20ga	18ga	1 - 1/2" Tie Rods	F @ 10'
44∅	<b>55x24</b>	38.98∅	20ga	18ga	1 - 1/2" Tie Rods	G @ 8'
46∅	<b>59x24</b>	39.29∅	20ga	18ga	1 - 1/2" Tie Rods	G @ 8'
48∅	<b>62x24</b>	40.24∅	20ga	16ga	1 - 1/2" Tie Rods	G @ 6'
50∅	<b>65x24</b>	41.15∅	20ga	16ga	2 - 1/2" Tie Rods	G @ 6'
52∅	<b>68x24</b>	42.03∅	20ga	16ga	2 - 1/2" Tie Rods	H @ 6'
54∅	<b>71x24</b>	42.98∅	18ga	16ga	2 - 1/2" Tie Rods	I @ 8'
56∅	<b>75x24</b>	43.99∅	18ga	16ga	2 - 1/2" Tie Rods	I @ 6'
58∅	<b>78x24</b>	44.63∅	18ga	16ga	2 - 1/2" Tie Rods	I @ 6'
60∅	<b>81x24</b>	45.45∅	18ga	16ga	2 - 1/2" Tie Rods	I @ 6'