



2" W.G. Flat Oval Construction For 8" Minor

Stock Diameter	Order Size	Equivalent Round	Spiral Seam Gauge	Fitting Gauge	<u>M/F Joint</u> *Optional Tie Rod for Easy Install	Reinforcement Max. Spacing
18Ø	24x8	14.39Ø	24ga	20ga	N/R	N/R
20Ø	27x8	15.19Ø	22ga	20ga	N/R	C @ 10'
22Ø	30x8	15.92Ø	22ga	20ga	N/R	D @ 10'
24Ø	33x8	16.61Ø	22ga	20ga	N/R	E @ 10'
26Ø	36x8	17.25Ø	22ga	20ga	1 - 1/2" Tie Rod	E @ 6'
28Ø	39x8	17.86Ø	22ga	18ga	1 - 1/2" Tie Rod	F @ 6'
30Ø	43x8	18.62Ø	22ga	18ga	1 - 1/2" Tie Rod	F @ 6'
32Ø	46x8	19.16Ø	22ga	18ga	1 - 1/2" Tie Rod	G @ 5'
34Ø	49x8	19.86Ø	22ga	18ga	1 - 1/2" Tie Rod	G @ 5'
36Ø	52x8	20.17Ø	20ga	18ga	1 - 1/2" Tie Rod	H @ 6'
38Ø	55x8	20.65Ø	20ga	18ga	1 - 1/2" Tie Rod	H @ 6'
40Ø	58x8	21.11Ø	20ga	18ga	1 - 1/2" Tie Rod	H @ 5'
42Ø	61x8	21.55Ø	20ga	16ga	2 - 1/2" Tie Rods	H @ 5'
44Ø	65x8	22.12Ø	20ga	16ga	2 - 1/2" Tie Rods	I @ 5'
46Ø	68x8	22.53Ø	20ga	16ga	2 - 1/2" Tie Rods	I @ 5'
48Ø	71x8	22.93Ø	18ga	16ga	2 - 1/2" Tie Rods	J @ 5'
50Ø	74x8	23.31Ø	18ga	16ga	2 - 1/2" Tie Rods	J @ 5'
52Ø	78x8	23.70Ø	18ga	16ga	2 - 1/2" Tie Rods	J @ 5'
54Ø	81x8	24.00Ø	18ga	16ga	2 - 1/2" Tie Rods	I @ 4'