



## 4" W.G. Flat Oval Construction For 12" Minor

Stock Diameter	Order Size	Equivalent Round	Spiral Seam Gauge	Fitting Gauge	<u>M/F Joint</u>	
					*Optional Tie Rod for Easy Install	Reinforcement Max. Spacing
18Ø	<b>22x12</b>	17.37Ø	22ga	20ga	N/R	N/R
20Ø	<b>25x12</b>	18.47Ø	22ga	20ga	N/R	C @ 8'
22Ø	<b>28x12</b>	19.16Ø	22ga	20ga	N/R	D @ 8'
24Ø	<b>31x12</b>	20.12Ø	22ga	20ga	N/R	E @ 6'
26Ø	<b>34x12</b>	21.02Ø	22ga	20ga	N/R	E @ 5'
28Ø	<b>37x12</b>	21.86Ø	22ga	18ga	1 - 1/2" Tie Rods	F @ 5'
30Ø	<b>40x12</b>	22.65Ø	22ga	18ga	1 - 1/2" Tie Rods	F @ 5'
32Ø	<b>43x12</b>	23.40Ø	22ga	18ga	1 - 1/2" Tie Rods	G @ 4'
34Ø	<b>47x12</b>	24.35Ø	22ga	18ga	1 - 1/2" Tie Rods	G @ 4'
36Ø	<b>50x12</b>	25.03Ø	20ga	18ga	1 - 1/2" Tie Rods	H @ 4'
38Ø	<b>53x12</b>	25.67Ø	20ga	18ga	1 - 1/2" Tie Rods	H @ 4'
40Ø	<b>56x12</b>	26.29Ø	20ga	18ga	1 - 1/2" Tie Rods	H @ 3'
42Ø	<b>59x12</b>	26.89Ø	20ga	18ga	1 - 1/2" Tie Rods	H @ 3'
44Ø	<b>62x12</b>	27.47Ø	20ga	16ga	2 - 1/2" Tie Rods	I @ 3'
46Ø	<b>65x12</b>	28.03Ø	20ga	16ga	2 - 1/2" Tie Rods	I @ 3'
48Ø	<b>69x12</b>	28.74Ø	20ga	16ga	2 - 1/2" Tie Rods	I @ 3'
50Ø	<b>72x12</b>	29.26Ø	18ga	16ga	2 - 1/2" Tie Rods	I @ 4'
52Ø	<b>75x12</b>	29.77Ø	18ga	16ga	2 - 1/2" Tie Rods	J @ 3'
54Ø	<b>78x12</b>	30.08Ø	18ga	16ga	2 - 1/2" Tie Rods	J @ 3'