



4" W.G. Flat Oval Construction For 14" Minor

Stock Diameter	Order Size	Equivalent Round	Spiral Seam Gauge	Fitting Gauge	<u>M/F Joint</u>	
					*Optional Tie Rod for Easy Install	Reinforcement Max. Spacing
18Ø	20x14	17.32Ø	24ga	20ga	N/R	N/R
20Ø	23x14	18.69Ø	22ga	20ga	N/R	N/R
22Ø	27x14	20.32Ø	22ga	20ga	N/R	C @ 8'
24Ø	30x14	21.43Ø	22ga	20ga	N/R	D @ 8'
26Ø	33x14	22.46Ø	22ga	20ga	N/R	E @ 6'
28Ø	36x14	23.42Ø	22ga	20ga	N/R	E @ 5'
30Ø	39x14	24.33Ø	22ga	18ga	1 - 1/2" Tie Rods	F @ 5'
32Ø	42x14	25.18Ø	22ga	18ga	1 - 1/2" Tie Rods	F @ 5'
34Ø	45x14	25.99Ø	22ga	18ga	1 - 1/2" Tie Rods	G @ 4'
36Ø	49x14	27.02Ø	20ga	18ga	1 - 1/2" Tie Rods	H @ 5'
38Ø	52x14	27.75Ø	20ga	18ga	1 - 1/2" Tie Rods	H @ 4'
40Ø	55x14	28.45Ø	20ga	18ga	1 - 1/2" Tie Rods	H @ 4'
42Ø	58x14	29.12Ø	20ga	18ga	1 - 1/2" Tie Rods	H @ 3'
44Ø	61x14	29.77Ø	20ga	16ga	2 - 1/2" Tie Rods	H @ 3'
46Ø	64x14	30.40Ø	20ga	16ga	2 - 1/2" Tie Rods	I @ 3'
48Ø	67x14	31.01Ø	20ga	16ga	2 - 1/2" Tie Rods	I @ 3'
50Ø	71x14	31.79Ø	18ga	16ga	2 - 1/2" Tie Rods	I @ 4'
52Ø	74x14	32.36Ø	18ga	16ga	2 - 1/2" Tie Rods	I @ 4'
54Ø	77x14	32.91Ø	18ga	16ga	2 - 1/2" Tie Rods	J @ 3'