



## 4" W.G. Flat Oval Construction For 16" Minor

Stock Diameter	Order Size	Equivalent Round	Spiral Seam Gauge	Fitting Gauge	<u>M/F Joint</u>	
					*Optional Tie Rod for Easy Install	Reinforcement Max. Spacing
20∅	<b>22x16</b>	19.38∅	24ga	20ga	N/R	N/R
22∅	<b>25x16</b>	20.80∅	22ga	20ga	N/R	N/R
24∅	<b>29x16</b>	22.50∅	22ga	20ga	N/R	C @ 8'
26∅	<b>32x16</b>	23.66∅	22ga	20ga	N/R	D @ 8'
28∅	<b>35x16</b>	24.74∅	22ga	20ga	N/R	E @ 6'
30∅	<b>38x16</b>	25.76∅	22ga	18ga	1 - 1/2" Tie Rods	E @ 5'
32∅	<b>41x16</b>	26.72∅	22ga	18ga	1 - 1/2" Tie Rods	F @ 5'
34∅	<b>44x16</b>	27.63∅	22ga	18ga	1 - 1/2" Tie Rods	F @ 5'
36∅	<b>47x16</b>	28.50∅	22ga	18ga	1 - 1/2" Tie Rods	G @ 4'
38∅	<b>51x16</b>	29.59∅	20ga	18ga	1 - 1/2" Tie Rods	H @ 5'
40∅	<b>54x16</b>	30.37∅	20ga	18ga	1 - 1/2" Tie Rods	H @ 4'
42∅	<b>57x16</b>	31.12∅	20ga	18ga	1 - 1/2" Tie Rods	H @ 4'
44∅	<b>60x16</b>	31.85∅	20ga	18ga	1 - 1/2" Tie Rods	H @ 3'
46∅	<b>63x16</b>	32.55∅	20ga	16ga	2 - 1/2" Tie Rods	H @ 3'
48∅	<b>66x16</b>	33.22∅	20ga	16ga	2 - 1/2" Tie Rods	I @ 3'
50∅	<b>69x16</b>	33.87∅	20ga	16ga	2 - 1/2" Tie Rods	I @ 3'
52∅	<b>73x16</b>	34.72∅	18ga	16ga	2 - 1/2" Tie Rods	I @ 4'
54∅	<b>76x16</b>	35.33∅	18ga	16ga	2 - 1/2" Tie Rods	I @ 4'
56∅	<b>79x16</b>	35.89∅	18ga	16ga	2 - 1/2" Tie Rods	J @ 3'