



4" W.G. Flat Oval Construction For 6" Minor

Stock Diameter	Order Size	Equivalent Round	Spiral Seam Gauge	Fitting Gauge	<u>M/F Joint</u>	Reinforcement Max. Spacing
					*Optional Tie Rod for Easy Install	
16∅	22 x 6	11.82∅	24ga	20ga	N/R	C @ 5'
18∅	25 x 6	12.51∅	22ga	20ga	N/R	E @ 6'
20∅	28 x 6	13.51∅	22ga	20ga	N/R	E @ 5'
22∅	31 x 6	13.73∅	22ga	20ga	N/R	F @ 5'
24∅	34 x 6	14.28∅	22ga	20ga	N/R	F @ 5'
26∅	37 x 6	14.80∅	22ga	18ga	1 - 1/2" Tie Rods	G @ 4'
28∅	41 x 6	15.45∅	22ga	18ga	1 - 1/2" Tie Rods	G @ 4'
30∅	44 x 6	15.90∅	22ga	18ga	1 - 1/2" Tie Rods	G @ 3'
32∅	47 x 6	16.34∅	22ga	18ga	1 - 1/2" Tie Rods	G @ 3'
34∅	50 x 6	16.76∅	20ga	18ga	1 - 1/2" Tie Rods	H @ 3'
36∅	53 x 6	17.16∅	20ga	18ga	1 - 1/2" Tie Rods	H @ 3'
38∅	56 x 6	17.55∅	20ga	18ga	1 - 1/2" Tie Rods	I @ 3'
40∅	59 x 6	17.92∅	20ga	18ga	1 - 1/2" Tie Rods	I @ 3'
42∅	63 x 6	18.40∅	20ga	16ga	2 - 1/2" Tie Rods	I @ 3'
44∅	66 x 6	18.75∅	20ga	16ga	2 - 1/2" Tie Rods	I @ 3'
46∅	69 x 6	19.08∅	20ga	16ga	2 - 1/2" Tie Rods	I @ 2.5'
48∅	72 x 6	19.41∅	18ga	16ga	2 - 1/2" Tie Rods	J @ 3'
50∅	75 x 6	19.73∅	18ga	16ga	2 - 1/2" Tie Rods	J @ 3'
52∅	79 x 6	21.60∅	18ga	16ga	2 - 1/2" Tie Rods	J @ 2.5'