



2" W.G. Flat Oval Construction For 10" Minor

Stock Diameter	Order Size	Equivalent Round	Spiral Seam Gauge	Fitting Gauge	M/F Joint *Optional Tie Rod for Easy Install	Reinforcement Max. Spacing
18Ø	23x10	15.85Ø	24ga	20ga	N/R	N/R
20Ø	26x10	16.82Ø	22ga	20ga	N/R	N/R
22Ø	29x10	17.17Ø	22ga	20ga	N/R	C @ 10'
24Ø	32x10	18.53Ø	22ga	20ga	N/R	D @ 10'
26Ø	35x10	19.30Ø	22ga	20ga	N/R	E @ 10'
28Ø	38x10	20.02Ø	22ga	18ga	1 - 1/2" Tie Rod	E @ 6'
30Ø	42x10	20.71Ø	22ga	18ga	1 - 1/2" Tie Rod	F @ 6'
32Ø	45x10	21.57Ø	22ga	18ga	1 - 1/2" Tie Rod	F @ 6'
34Ø	48x10	22.18Ø	22ga	18ga	1 - 1/2" Tie Rod	G @ 5'
36Ø	51x10	22.76Ø	20ga	18ga	1 - 1/2" Tie Rod	G @ 6'
38Ø	54x10	23.32Ø	20ga	18ga	1 - 1/2" Tie Rod	H @ 6'
40Ø	58x10	23.86Ø	20ga	18ga	1 - 1/2" Tie Rod	H @ 6'
42Ø	61x10	24.39Ø	20ga	16ga	2 - 1/2" Tie Rods	H @ 5'
44Ø	64x10	24.89Ø	20ga	16ga	2 - 1/2" Tie Rods	H @ 5'
46Ø	67x10	25.54Ø	20ga	16ga	2 - 1/2" Tie Rods	I @ 5'
48Ø	70x10	26.00Ø	20ga	16ga	2 - 1/2" Tie Rods	I @ 5'
50Ø	73x10	26.46Ø	18ga	16ga	2 - 1/2" Tie Rods	J @ 5'
52Ø	76x10	26.90Ø	18ga	16ga	2 - 1/2" Tie Rods	J @ 5'
54Ø	80x10	27.35Ø	18ga	16ga	2 - 1/2" Tie Rods	J @ 5'

*Reinforcement requires either one internal tie rod, or two external tie rods.