



2" W.G. Flat Oval Construction For 16" Minor

Stock Diameter	Order Size	Equivalent Round	Spiral Seam Gauge	Fitting Gauge	<u>M/F Joint</u> *Optional Tie Rod for Easy Install	Reinforcement Max. Spacing
20Ø	22X16	19.38Ø	24ga	20ga	N/R	N/R
22Ø	25X16	20.80Ø	22ga	20ga	N/R	N/R
24Ø	29X16	22.50Ø	22ga	20ga	N/R	N/R
26Ø	32X16	23.66Ø	22ga	20ga	N/R	N/R
28Ø	35X16	24.74Ø	22ga	20ga	N/R	C @ 10'
30Ø	38X16	25.60Ø	22ga	18ga	1 - 1/2" Tie Rods	D @ 10'
32Ø	41X16	26.72Ø	22ga	18ga	1 - 1/2" Tie Rods	E @ 10'
34Ø	45X16	27.36Ø	22ga	18ga	1 - 1/2" Tie Rods	E @ 6'
36Ø	48X16	28.50Ø	22ga	18ga	1 - 1/2" Tie Rods	F @ 6'
38Ø	51X16	29.59Ø	20ga	18ga	1 - 1/2" Tie Rods	G @ 8'
40Ø	54X16	30.37Ø	20ga	18ga	1 - 1/2" Tie Rods	G @ 6'
42Ø	57X16	31.12Ø	20ga	18ga	1 - 1/2" Tie Rods	G @ 6'
44Ø	60X16	31.85Ø	20ga	18ga	1 - 1/2" Tie Rods	H @ 6'
46Ø	64X16	32.55Ø	20ga	16ga	2 - 1/2" Tie Rods	H @ 6'
48Ø	67X16	33.22Ø	20ga	16ga	2 - 1/2" Tie Rods	H @ 5'
50Ø	70X16	33.87Ø	20ga	16ga	2 - 1/2" Tie Rods	H @ 5'
52Ø	73X16	34.72Ø	18ga	16ga	2 - 1/2" Tie Rods	I @ 6'
54Ø	76X16	35.33Ø	18ga	16ga	2 - 1/2" Tie Rods	I @ 6'
56Ø	79X16	35.89Ø	18ga	16ga	2 - 1/2" Tie Rods	J @ 5'

*Reinforcement requires either one internal tie rod, or two external tie rods.