



2" W.G. Flat Oval Construction For 18" Minor

Stock Diameter	Order Size	Equivalent Round	Spiral Seam Gauge	Fitting Gauge	<u>M/F Joint</u> *Optional Tie Rod for Easy Install	Reinforcement Max. Spacing
22Ø	24X18	21.42Ø	24ga	20ga	N/R	N/R
24Ø	28X18	22.88Ø	22ga	20ga	N/R	N/R
26Ø	31X18	24.64Ø	22ga	20ga	N/R	N/R
28Ø	34X18	28.85Ø	22ga	20ga	N/R	N/R
30Ø	37X18	26.99Ø	22ga	18ga	1 - 1/2" Tie Rods	C @ 10'
32Ø	40X18	28.05Ø	22ga	18ga	1 - 1/2" Tie Rods	D @ 10'
34Ø	43X18	29.06Ø	22ga	18ga	1 - 1/2" Tie Rods	E @ 10'
36Ø	47X18	30.02Ø	22ga	18ga	1 - 1/2" Tie Rods	E @ 6'
38Ø	50X18	30.94Ø	20ga	18ga	1 - 1/2" Tie Rods	G @ 8'
40Ø	53X18	32.10Ø	20ga	18ga	1 - 1/2" Tie Rods	G @ 8'
42Ø	56X18	32.92Ø	20ga	18ga	1 - 1/2" Tie Rods	G @ 6'
44Ø	59X18	33.72Ø	20ga	18ga	1 - 1/2" Tie Rods	G @ 6'
46Ø	62X18	34.49Ø	20ga	16ga	2 - 1/2" Tie Rods	H @ 6'
48Ø	66X18	35.23Ø	20ga	16ga	2 - 1/2" Tie Rods	H @ 6'
50Ø	69X18	35.95Ø	20ga	16ga	2 - 1/2" Tie Rods	H @ 5'
52Ø	72X18	36.87Ø	18ga	16ga	2 - 1/2" Tie Rods	I @ 6'
54Ø	75X18	37.54Ø	18ga	16ga	2 - 1/2" Tie Rods	I @ 6'
56Ø	78X18	38.12Ø	18ga	16ga	2 - 1/2" Tie Rods	I @ 6'
58Ø	81X18	38.79Ø	18ga	16ga	2 - 1/2" Tie Rods	J @ 5'

*Reinforcement requires either one internal tie rod, or two external tie rods.