



## 2" W.G. Flat Oval Construction For 20" Minor

Stock Diameter	Order Size	Equivalent Round	Spiral Seam Gauge	Fitting Gauge	M/F Joint *Optional Tie Rod for Easy Install	Reinforcement Max. Spacing
24Ø	<b>26X20</b>	23.46Ø	22ga	20ga	N/R	N/R
26Ø	<b>30X20</b>	24.95Ø	22ga	20ga	N/R	N/R
28Ø	<b>33X20</b>	26.77Ø	22ga	20ga	N/R	N/R
30Ø	<b>36X20</b>	28.02Ø	22ga	20ga	N/R	N/R
32Ø	<b>39X20</b>	29.20Ø	22ga	18ga	1 - 1/2" Tie Rods	C @ 10'
34Ø	<b>42X20</b>	30.31Ø	22ga	18ga	1 - 1/2" Tie Rods	D @ 10'
36Ø	<b>45X20</b>	31.36Ø	22ga	18ga	1 - 1/2" Tie Rods	E @ 10'
38Ø	<b>49X20</b>	32.37Ø	20ga	18ga	1 - 1/2" Tie Rods	F @ 10'
40Ø	<b>52X20</b>	33.32Ø	20ga	18ga	1 - 1/2" Tie Rods	G @ 8'
42Ø	<b>55X20</b>	34.54Ø	20ga	18ga	1 - 1/2" Tie Rods	G @ 8'
44Ø	<b>58X20</b>	35.41Ø	20ga	18ga	1 - 1/2" Tie Rods	G @ 6'
46Ø	<b>61X20</b>	36.25Ø	20ga	16ga	2 - 1/2" Tie Rods	G @ 6'
48Ø	<b>64X20</b>	37.06Ø	20ga	16ga	2 - 1/2" Tie Rods	H @ 6'
50Ø	<b>68X20</b>	37.84Ø	20ga	16ga	2 - 1/2" Tie Rods	H @ 6'
52Ø	<b>71X20</b>	38.84Ø	18ga	16ga	2 - 1/2" Tie Rods	I @ 6'
54Ø	<b>74X20</b>	39.57Ø	18ga	16ga	2 - 1/2" Tie Rods	I @ 6'
56Ø	<b>77X20</b>	40.17Ø	18ga	16ga	2 - 1/2" Tie Rods	I @ 6'
58Ø	<b>80X20</b>	40.90Ø	18ga	16ga	2 - 1/2" Tie Rods	I @ 6'
60Ø	<b>83X20</b>	41.60Ø	18ga	16ga	2 - 1/2" Tie Rods	J @ 5'

\*Reinforcement requires either one internal tie rod, or two external tie rods.