



2" W.G. Flat Oval Construction For 24" Minor

Stock Diameter	Order Size	Equivalent Round	Spiral Seam Gauge	Fitting Gauge	M/F Joint *Optional Tie Rod for Easy Install	Reinforcement Max. Spacing
28∅	30x24	27.52∅	22ga	20ga	N/R	N/R
30∅	34x24	29.07∅	22ga	20ga	N/R	N/R
32∅	37x24	30.97∅	22ga	18ga	1 - 1/2" Tie Rods	N/R
34∅	40x24	32.29∅	22ga	18ga	1 - 1/2" Tie Rods	N/R
36∅	43x24	33.54∅	22ga	18ga	1 - 1/2" Tie Rods	C @ 10'
38∅	46x24	34.73∅	22ga	18ga	1 - 1/2" Tie Rods	D @ 10'
40∅	49x24	35.86∅	20ga	8ga	1 - 1/2" Tie Rods	E @ 10'
42∅	53x24	36.94∅	20ga	18ga	1 - 1/2" Tie Rods	F @ 10'
44∅	56x24	38.98∅	20ga	18ga	1 - 1/2" Tie Rods	G @ 8'
46∅	59x24	39.29∅	20ga	18ga	1 - 1/2" Tie Rods	G @ 8'
48∅	62x24	40.24∅	20ga	16ga	1 - 1/2" Tie Rods	G @ 6'
50∅	65x24	41.15∅	20ga	16ga	2 - 1/2" Tie Rods	G @ 6'
52∅	68x24	42.03∅	20ga	16ga	2 - 1/2" Tie Rods	H @ 6'
54∅	72x24	42.98∅	18ga	16ga	2 - 1/2" Tie Rods	I @ 8'
56∅	75x24	43.99∅	18ga	16ga	2 - 1/2" Tie Rods	I @ 6'
58∅	78x24	44.63∅	18ga	16ga	2 - 1/2" Tie Rods	I @ 6'
60∅	81x24	45.45∅	18ga	16ga	2 - 1/2" Tie Rods	I @ 6'

*Reinforcement requires either one internal tie rod, or two external tie rods.