



## 2" W.G. Flat Oval Construction For 6" Minor

Stock Diameter	Order Size	Equivalent Round	Spiral Seam Gauge	Fitting Gauge	<u>M/F Joint</u> *Optional Tie Rod for Easy Install	Reinforcement Max. Spacing
16Ø	<b>22 x 6</b>	11.82Ø	24ga	20ga	N/R	N/R
18Ø	<b>25 x 6</b>	12.51Ø	22ga	20ga	N/R	C @ 10'
20Ø	<b>28 x 6</b>	13.51Ø	22ga	20ga	N/R	D @ 10'
22Ø	<b>31 x 6</b>	13.73Ø	22ga	20ga	N/R	E @ 10'
24Ø	<b>35 x 6</b>	14.28Ø	22ga	20ga	N/R	E @ 6'
26Ø	<b>38 x 6</b>	14.80Ø	22ga	18ga	1 - 1/2" Tie Rod	F @ 6'
28Ø	<b>41 x 6</b>	15.45Ø	22ga	18ga	1 - 1/2" Tie Rod	F @ 6'
30Ø	<b>44 x 6</b>	15.90Ø	22ga	18ga	1 - 1/2" Tie Rod	G @ 5'
32Ø	<b>47 x 6</b>	16.34Ø	22ga	18ga	1 - 1/2" Tie Rod	G @ 5'
34Ø	<b>50 x 6</b>	16.76Ø	20ga	18ga	1 - 1/2" Tie Rod	H @ 6'
36Ø	<b>54 x 6</b>	17.16Ø	20ga	18ga	1 - 1/2" Tie Rod	H @ 6'
38Ø	<b>57 x 6</b>	17.55Ø	20ga	18ga	1 - 1/2" Tie Rod	H @ 5'
40Ø	<b>60 x 6</b>	17.92Ø	20ga	18ga	1 - 1/2" Tie Rod	H @ 5'
42Ø	<b>63 x 6</b>	18.40Ø	20ga	16ga	2 - 1/2" Tie Rods	I @ 5'
44Ø	<b>66 x 6</b>	18.75Ø	20ga	16ga	2 - 1/2" Tie Rods	I @ 5'
46Ø	<b>69 x 6</b>	19.08Ø	20ga	16ga	2 - 1/2" Tie Rods	I @ 4'
48Ø	<b>72 x 6</b>	19.41Ø	18ga	16ga	2 - 1/2" Tie Rods	J @ 5'
50Ø	<b>76 x 6</b>	19.73Ø	18ga	16ga	2 - 1/2" Tie Rods	J @ 5'
52Ø	<b>79 x 6</b>	21.60Ø	18ga	16ga	2 - 1/2" Tie Rods	I @ 4'

\*Reinforcement requires either one internal tie rod, or two external tie rods.