



## 4" W.G. Flat Oval Construction For 14" Minor

Stock Diameter	Order Size	Equivalent Round	Spiral Seam Gauge	Fitting Gauge	<u>M/F Joint</u>	
					*Optional Tie Rod for Easy Install	Reinforcement Max. Spacing
18Ø	<b>20X14</b>	17.32Ø	24ga	20ga	N/R	N/R
20Ø	<b>24X14</b>	18.69Ø	22ga	20ga	N/R	N/R
22Ø	<b>27X14</b>	20.32Ø	22ga	20ga	N/R	C @ 8'
24Ø	<b>30X14</b>	21.43Ø	22ga	20ga	N/R	D @ 8'
26Ø	<b>33X14</b>	22.46Ø	22ga	20ga	N/R	E @ 6'
28Ø	<b>36X14</b>	23.42Ø	22ga	20ga	N/R	E @ 5'
30Ø	<b>39X14</b>	24.33Ø	22ga	18ga	1 - 1/2" Tie Rods	F @ 5'
32Ø	<b>43X14</b>	25.18Ø	22ga	18ga	1 - 1/2" Tie Rods	F @ 5'
34Ø	<b>46X14</b>	25.99Ø	22ga	18ga	1 - 1/2" Tie Rods	G @ 4'
36Ø	<b>49X14</b>	27.02Ø	20ga	18ga	1 - 1/2" Tie Rods	H @ 5'
38Ø	<b>52X14</b>	27.75Ø	20ga	18ga	1 - 1/2" Tie Rods	H @ 4'
40Ø	<b>55X14</b>	28.45Ø	20ga	18ga	1 - 1/2" Tie Rods	H @ 4'
42Ø	<b>58X14</b>	29.12Ø	20ga	18ga	1 - 1/2" Tie Rods	H @ 3'
44Ø	<b>62X14</b>	29.77Ø	20ga	16ga	2 - 1/2" Tie Rods	H @ 3'
46Ø	<b>65X14</b>	30.40Ø	20ga	16ga	2 - 1/2" Tie Rods	I @ 3'
48Ø	<b>68X14</b>	31.01Ø	20ga	16ga	2 - 1/2" Tie Rods	I @ 3'
50Ø	<b>71X14</b>	31.79Ø	18ga	16ga	2 - 1/2" Tie Rods	I @ 4'
52Ø	<b>74X14</b>	32.36Ø	18ga	16ga	2 - 1/2" Tie Rods	I @ 4'
54Ø	<b>77X14</b>	32.91Ø	18ga	16ga	2 - 1/2" Tie Rods	J @ 3'

\*Reinforcement requires either one internal tie rod, or two external tie rods.