



4" W.G. Flat Oval Construction For 16" Minor

Stock Diameter	Order Size	Equivalent Round	Spiral Seam Gauge	Fitting Gauge	<u>M/F Joint</u>	Reinforcement Max. Spacing
					*Optional Tie Rod for Easy Install	
20∅	22X16	19.38∅	24ga	20ga	N/R	N/R
22∅	25X16	20.80∅	22ga	20ga	N/R	N/R
24∅	29X16	22.50∅	22ga	20ga	N/R	C @ 8'
26∅	32X16	23.66∅	22ga	20ga	N/R	D @ 8'
28∅	35X16	24.74∅	22ga	20ga	N/R	E @ 6'
30∅	38X16	25.76∅	22ga	18ga	1 - 1/2" Tie Rods	E @ 5'
32∅	41X16	26.72∅	22ga	18ga	1 - 1/2" Tie Rods	F @ 5'
34∅	45X16	27.63∅	22ga	18ga	1 - 1/2" Tie Rods	F @ 5'
36∅	48X16	28.50∅	22ga	18ga	1 - 1/2" Tie Rods	G @ 4'
38∅	51X16	29.59∅	20ga	18ga	1 - 1/2" Tie Rods	H @ 5'
40∅	54X16	30.37∅	20ga	18ga	1 - 1/2" Tie Rods	H @ 4'
42∅	57X16	31.12∅	20ga	18ga	1 - 1/2" Tie Rods	H @ 4'
44∅	60X16	31.85∅	20ga	18ga	1 - 1/2" Tie Rods	H @ 3'
46∅	64X16	32.55∅	20ga	16ga	2 - 1/2" Tie Rods	H @ 3'
48∅	67X16	33.22∅	20ga	16ga	2 - 1/2" Tie Rods	I @ 3'
50∅	70X16	33.87∅	20ga	16ga	2 - 1/2" Tie Rods	I @ 3'
52∅	73X16	34.72∅	18ga	16ga	2 - 1/2" Tie Rods	I @ 4'
54∅	76X16	35.33∅	18ga	16ga	2 - 1/2" Tie Rods	I @ 4'
56∅	79X16	35.89∅	18ga	16ga	2 - 1/2" Tie Rods	J @ 3'

*Reinforcement requires either one internal tie rod, or two external tie rods.