



4" W.G. Flat Oval Construction For 6" Minor

Stock Diameter	Order Size	Equivalent Round	Spiral Seam Gauge	Fitting Gauge	<u>M/F Joint</u>	Reinforcement Max. Spacing
					*Optional Tie Rod for Easy Install	
16Ø	22 x 6	11.82Ø	24ga	20ga	N/R	C @ 5'
18Ø	25 x 6	12.51Ø	22ga	20ga	N/R	E @ 6'
20Ø	28 x 6	13.51Ø	22ga	20ga	N/R	E @ 5'
22Ø	31 x 6	13.73Ø	22ga	20ga	N/R	F @ 5'
24Ø	35 x 6	14.28Ø	22ga	20ga	N/R	F @ 5'
26Ø	38 x 6	14.80Ø	22ga	18ga	1 - 1/2" Tie Rods	G @ 4'
28Ø	41 x 6	15.45Ø	22ga	18ga	1 - 1/2" Tie Rods	G @ 4'
30Ø	44 x 6	15.90Ø	22ga	18ga	1 - 1/2" Tie Rods	G @ 3'
32Ø	47 x 6	16.34Ø	22ga	18ga	1 - 1/2" Tie Rods	G @ 3'
34Ø	50 x 6	16.76Ø	20ga	18ga	1 - 1/2" Tie Rods	H @ 3'
36Ø	54 x 6	17.16Ø	20ga	18ga	1 - 1/2" Tie Rods	H @ 3'
38Ø	57 x 6	17.55Ø	20ga	18ga	1 - 1/2" Tie Rods	I @ 3'
40Ø	60 x 6	17.92Ø	20ga	18ga	1 - 1/2" Tie Rods	I @ 3'
42Ø	63 x 6	18.40Ø	20ga	16ga	2 - 1/2" Tie Rods	I @ 3'
44Ø	66 x 6	18.75Ø	20ga	16ga	2 - 1/2" Tie Rods	I @ 3'
46Ø	69 x 6	19.08Ø	20ga	16ga	2 - 1/2" Tie Rods	I @ 2.5'
48Ø	72 x 6	19.41Ø	18ga	16ga	2 - 1/2" Tie Rods	J @ 3'
50Ø	76 x 6	19.73Ø	18ga	16ga	2 - 1/2" Tie Rods	J @ 3'
52Ø	79 x 6	21.60Ø	18ga	16ga	2 - 1/2" Tie Rods	J @ 2.5'

*Reinforcement requires either one internal tie rod, or two external tie rods.